

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

JUN 27 1975

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

NOTE  
WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Freeman

2. LOCATION - 1/4 Section SE Section 16 Township 10N Range 6W 3. OWNER AT TIME OF DRILLING James Finley  
OR - Grid or street no. Street name ADDRESS Ferryville

AND - If available subdivision name, lot & block no. POST OFFICE Wis., 54628

4. Distance in feet from well to nearest: (Record answer in appropriate block)

BUILDING C.I.	SANITARY SEWER C.I.	SEWER TILE	FLOOR DRAIN C.I.	FLOOR DRAIN TILE	FOUNDATION DRAIN SEWER CONNECTED	FOUNDATION DRAIN INDEPENDENT	WASTE WATER DRAIN C.I.	WASTE WATER DRAIN TILE
	100'	100'						

CLEAR WATER DRAIN C.I.	CLEAR WATER DRAIN TILE	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILO	ABANDONED WELL	SINK HOLE
		125'			140'	130'			

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Farm home

6. DRILLHOLE			9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
6	Surface	125			

7. CASING, LINER, CURBING, AND SCREEN			
Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
6	new black steel plain end 18.97	Surface	113

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
loose sand	Surface	100

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Direct Rotary  Reverse Rotary  
 Rotary - air w/drilling mud  Rotary - hammer with drilling mud & air  Jetting with Air  Water

Well construction completed on 6-9-1975

11. MISCELLANEOUS DATA

Yield test: 5 Hrs. at 5 GPM

Well is terminated 8 inches  above  below final grade

Depth from surface to normal water level 75 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 90 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 6-24-1975

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Copian Registered Well Driller COMPLETE MAIL ADDRESS Boscobel, Wis., 53805

COLIFORM TEST RESULT 1030 GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS

REV. 3-71