

SPOT CHECK

NOTE:
White Copy - Division's Copy
Green Copy - Driller's Copy
Yellow Copy - Owner's Copy

JUN 23 1982

1. COUNTY Crawford CHECK (✓) ONE: Town Village City Name Freeman

2. LOCATION SW of NW Section 10 Township 10N Range 6W 3. NAME OWNER AGENT AT TIME OF DRILLING CHECK (✓) ONE
Robert W Rowan

OR - Grid or Street No. Street or Road Name ADDRESS 5315 West National Ave.

AND - If available subdivision name, lot & block No. POST OFFICE West Milwaukee W. ZIP CODE 53214

4. Distance in feet from well to nearest: (Record answer in appropriate block) 60'

Building		Sanitary Bldg. Drain		Sanitary Bldg. Sewer		Floor Drain Connected To:		Storm Bldg. Drain		Storm Bldg. Sewer	
C.I.	Other	C.I.	Other	C.I.	Other	C.I. Sewer	Other Sewer	C.I.	Other	C.I.	Other

Street Sewer		Other Sewers		Foundation Drain Connected to:		Sewage Sump		Clearwater Sump		Septic Tank		Holding Tank		Sewage Absorption Unit		Manure Hopper or Retention or Pneumatic Tank		
San.	Storm	C.I.	Other	Sewer	Clearwater Dr.	Sewage Sump	Clearwater Sump	C.I.	Other	C.I.	Other	C.I.	Other	Seepage Pit	Seepage Bed	Seepage Trench		

Privy		Pet Waste Pit		Pit: Nonconforming Existing		Subsurface Pumphouse		Barn Gutter		Animal Barn Pen		Animal Yard		Silo With Pit		Glass Lined Storage Facility		Silo w/o Pit		Earthen Silage Storage Trench Or Pit		Earthen Manure Basin	
				Well	Pump																		

Temporary Manure Stack or Platform		Watertight Liquid Manure Tank or Basin		Manure Pressure Pipe		Subsurface Gasoline or Oil Tank		Waste Pond or Land Disposal Unit (Specify Type)		Manure Storage Basin		Other (Describe)	
										Concrete Floor Only	Concrete Floor and Partial Concrete Walls		

5. Well is intended to supply water for: Country home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
10	Surface	62	6	62	160

9. FORMATIONS

Kind	From (ft.)	To (ft.)
clay	Surface	10
shale	10	110
sand rock	110	160

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification	From (ft.)	To (ft.)
6	new black steel PE 18.97	Surface	62
	A-53 Valley Steel Pithis adaptor		

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
clay	Surface	8
cement	8	62

10. TYPE OF DRILLING MACHINE USED

Cable Tool Rotary-hammer w/drilling mud & air Jetting with

Rotary-air w/drilling mud Rotary-hammer & air Air

Rotary-w/drilling mud Reverse Rotary Water

11. MISCELLANEOUS DATA

Yield Test: 3 Hrs. at 7 GPM Well is terminated 12 inches above final grade below

Depth from surface to normal water level 120 Ft. Well disinfected upon completion Yes No

Depth of water level when pumping 122 Ft. Stabilized Yes No Well sealed watertight upon completion Yes No

Water sample sent to Madison Wi laboratory on 6-15 1982

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Donald C. Kirschbaum Registered Well Driller Business Name and Complete Mailing Address Pt 4 Box 75 Dons Well Drilling Boscobel Wis 53805

193