

# WELL LOG and REPORT

For method of making report, refer to bulletin entitled "Well Construction Report," 7-5-39.

In this column indicate the kind of casing, liner, shoe and other accessories used.

**WELL DIAGRAM**  
Use a red line to show casing or liner pipe. Use black for drill or borehole.

In this column state the kind of formations penetrated, their thickness in feet and if water bearing.

Record of  
FINAL  
Pumping test

Steel  
Casing

Inches Diameter	Depth
2 3 4 5 6 8 10 12 14 16 18	
7" (dashed line)	25
(dashed line)	50
(dashed line)	54
(dashed line)	75
(dashed line)	100
(dashed line)	150
(dashed line)	170
(dashed line)	200
(dashed line)	400
(dashed line)	800
(dashed line)	1200

Clay

Flint layers

sandy limestone

See letter re:  
nonperformance  
12-9-41

Duration of test  
Hours 4

Pumping rate  
G.P.M. 5

Depth of pump in well. Ft. 168

Standing water-level (from surface)  
Ft. 154

Water-level when pumping Ft. don't know

Water. End of test.  
Clear   
Cloudy \_\_\_\_\_  
Turbid \_\_\_\_\_

Was the well sterilized?  
Yes \_\_\_\_\_ No

To which laboratory was sample sent?  
Madison  
Date Nov 28

Was the well sealed on completion?  
Yes \_\_\_\_\_ No

How high did you leave the casing-pipe above grade?  
6"

Well was completed  
Date Nov 10

Well Constructor  
Joe Sall  
Signature

Draw the diagram to show the right half only