

WELL CONSTRUCTOR'S REPORT

Well-6

WHITE COPY - DIVISION'S COPY
GREEN COPY - DRILLER'S COPY
YELLOW COPY - OWNER'S COPY

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
Box 450
Madison, Wisconsin 53701

JUL 15 1971

1. COUNTY Crawford CHECK ONE Town Village City NAME Wauseka

2. LOCATION (Number and Street or 1/4 section, section, township and range. Also give subdivision name, lot and block numbers when available.)
SW 1/4 of Sec. 16 T 7N R 5W

3. OWNER AT TIME OF DRILLING
Louis F. Scherman

4. OWNER'S COMPLETE MAIL ADDRESS
RFD Wauseka, Wis. 53826

5. Distance in feet from well to nearest:

BUILDING C.I. TILE	SANITARY SEWER C.I. TILE	FLOOR DRAIN C.I. TILE	FOUNDATION DRAIN SEWER CONNECTED	FOUNDATION DRAIN INDEPENDENT	WASTE WATER DRAIN C.I. TILE			
10'	10'				10'			
CLEAR WATER DRAIN C.I. TILE	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILLO	ABANDONED WELL	SINK HOLE
	70'			85'				

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

6. Well is intended to supply water for: Trailer home

7. DRILLHOLE						10. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
10	Surface	63	6	63	100	Clay	Surface	12
						loose limestone	12	50
						hard sandstone	50	100

8. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
6	new black steel plain end 19.18	Surface	63

9. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
Clay	Surface	12
Cement	12	63

11. MISCELLANEOUS DATA

Yield test: 5 Hrs. at 8 GPM

Well is terminated 12 inches above below final grade

Depth from surface to normal water level 49 ft. Well disinfected upon completion Yes No

Depth to water level when pumping 55 ft. Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on: 7-12- 1971

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Denneth Coysian Registered Well Driller COMPLETE MAIL ADDRESS Boocobal, R3 Box 84 Wis., 53805

Please do not write in space below

COLIFORM TEST RESULT <u>363</u>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
------------------------------------	---------------	---------------	-----------	---------