

JAN 10 1974

WELL CONSTRUCTOR'S REPORT
FORM 3300-15

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
Box 450
Madison, Wisconsin 53701

NOTE
WHITE COPY - DIVISION'S COPY
GREEN COPY - DRILLER'S COPY
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE Town Village City NAME Wauzeka

2. LOCATION - 1/4 Section NE Section 22 Township 7N Range 5W
OR - Grid or street no. Street name
3. OWNER AT TIME OF DRILLING Mr. Ralph Bowman
ADDRESS Box 318 R7D

AND - If available subdivision name, lot & block no. POST OFFICE Wauzeka, Wis., 53826

4. Distance in feet from well to nearest:
(Record answer in appropriate block)

BUILDING C. I.	SANITARY SEWER TILE	FLOOR DRAIN C. I.	FOUNDATION DRAIN SEWER CONNECTED	FOUNDATION DRAIN INDEPENDENT	WASTE WATER DRAIN C. I.	WASTE WATER DRAIN TILE		
<u>15'</u>	<u>25'</u>				<u>25'</u>			
CLEAR WATER DRAIN C. I.	SEPTIC TANK TILE	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILO	ABANDONED WELL	SINK HOLE
	<u>50'</u>		<u>65'</u>				<u>25'</u>	

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	9. FORMATIONS Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>51</u>	<u>6</u>	<u>51</u>	<u>80</u>	<u>Clay</u>	<u>Surface</u>	<u>10</u>
						<u>soft sandstone</u>	<u>10</u>	<u>20</u>
						<u>hard sandstone</u>	<u>20</u>	<u>65</u>
						<u>limestone</u>	<u>65</u>	<u>80</u>

7. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
<u>6</u>	<u>plain end 19.18 new black steel</u>	<u>Surface</u>	<u>51</u>

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Clay</u>	<u>Surface</u>	<u>10</u>
<u>Cement</u>	<u>10</u>	<u>51</u>

10. TYPE OF DRILLING MACHINE USED
 Cable Tool Direct Rotary Reverse Rotary
 Rotary - air w/drilling mud Rotary - hammer with drilling mud & air Jetting with Air Water

11. MISCELLANEOUS DATA

Yield test: 3 Hrs. at 5 GPM

Well construction completed on 12-22-1973

Well is terminated 12 inches above below final grade

Depth from surface to normal water level 40 ft. Well disinfected upon completion Yes No

Depth to water level when pumping 48 ft. Well sealed watertight upon completion Yes No

Water sample sent to Madison, Wis. laboratory on: 1-7-1974

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumphrooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS Booscobel, R3 Box 84 Wis., 53805

Please do not write in space below

COLIFORM TEST RESULT <u>370</u>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
------------------------------------	---------------	---------------	-----------	---------

REV. 3-71