

# WELL LOG and REPORT

In this column indicate the kind of casing, liner, shoe and other accessories used.

**WELL DIAGRAM**  
Use a red line to show casing or liner pipe. Use black for drill or borehole.

In this column state the kind of formations penetrated, their thickness in feet and if water bearing.

Record of **FINAL** Pumping test

Standard 6 inch casing, and Drive shoe. Duplex Pump stand

Inches Diameter		Depth
2 3 4 5 6 8 10 12 14 16 18		
		15
		25
		50
		68
		75
		81
		100
		150
		200
		400
		800
		1200

15 ft surface clay.

gravel and quick sand. 53 ft

13 ft of shale & Rock

Duration of test  
Hours 4 hours

Pumping rate  
G.P.M. 20 gal

Depth of pump in well. Ft. 26

Standing water-level (from surface)  
Ft. 19

Water-level when pumping Ft. 19

Water. End of test.  
Clear   
Cloudy \_\_\_\_\_  
Turbid \_\_\_\_\_

Was the well sterilized?  
Yes  No \_\_\_\_\_

To which laboratory was sample sent?  
state  
Date 24

Was the well sealed on completion?  
Yes  No \_\_\_\_\_

How high did you leave the casing-pipe above grade?  
1 ft

Well was completed  
Date Jan 2, 1940

Well Driller  
E. S. Watson  
Signature

Draw the diagram to show the right half only