

WELL CONSTRUCTOR'S REPORT
FORM 3300-15

SEP 27 1973

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
Box 450
Madison, Wisconsin 53701

NOTE

WHITE COPY - DIVISION'S COPY
GREEN COPY - DRILLER'S COPY
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE Town Village City NAME Marietta

2. LOCATION - 1/4 Section NW Section 1 Township T8N Range R4W 3. OWNER AT TIME OF DRILLING James Cooper

OR - Grid or street no. Street name ADDRESS

AND - If available subdivision name, lot & block no. POST OFFICE Buscobel

4. Distance in feet from well to nearest: (Record answer in appropriate block)

BUILDING C.I.	SANITARY SEWER TILE	FLOOR DRAIN C.I.	TILE	FOUNDATION DRAIN SEWER CONNECTED	INDEPENDENT	WASTE WATER DRAIN C.I.	TILE
<u>8</u>							

CLEAR WATER DRAIN C.I.	TILE	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILO	ABANDONED WELL	SINK HOLE
		<u>60</u>							

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>170</u>				<u>Clay</u>	<u>Surface</u>	<u>5</u>
<u>6</u>	<u>170</u>	<u>520</u>				<u>St. Peter Sand</u>	<u>5</u>	<u>60</u>
						<u>Mag lime</u>	<u>60</u>	<u>300</u>
						<u>Cambrian Sandstone</u>	<u>300</u>	<u>445</u>
						<u>Francois Lime</u>	<u>445</u>	<u>470</u>
						<u>Sandstone</u>	<u>470</u>	<u>520</u>

7. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
<u>6</u>	<u>New Steel T+C 19.18</u>	<u>Surface</u>	<u>170</u>

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Cement</u>	<u>Surface</u>	<u>170</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool Direct Rotary Reverse Rotary

Rotary - air w/drilling mud Rotary - hammer with drilling mud & air Jetting with Air Water

Well construction completed on 8-25 1973

11. MISCELLANEOUS DATA

Yield test: 2 Hrs. at 15 GPM

Well is terminated 8 inches above below final grade

Depth from surface to normal water level 380 ft. Well disinfected upon completion Yes No

Depth to water level when pumping 420 ft. Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on: Sept 25 1973

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Ralph Faherty Registered Well Driller COMPLETE MAIL ADDRESS FAHERTY DRILLING CO., INC.
1120 Broadway
PLATTEVILLE, WISCONSIN 53818

Please do not write in space below

COLIFORM TEST RESULT <u>526</u> REV. 3-71	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
---	---------------	---------------	-----------	---------