

# WELL LOG and REPORT

For method of making report, refer to bulletin entitled "Well Construction Report," 7-5-39.

In this column indicate the kind of casing, liner, shoe and other accessories used.

**WELL DIAGRAM**  
Use a red line to show casing or liner pipe. Use black for drill or borehole.

In this column state the kind of formations penetrated, their thickness in feet and if water bearing.

Record of  
**FINAL**  
Pumping test

6" heavy Gas  
Pipe casing -  
Grouted with  
cement.  
68 ft casing

Inches Diameter		Depth
2 3 4 5 6 8 10 12 14 16 18		
		25
		40
		50
		68
		75
		80
		100
		150
		200
		400
		800
		1200

Topsoil & Clay  
  
Rock & Clay  
Layers  
  
Hard limestone

Duration of test  
Hours 1

Pumping rate  
G.P.M. 5

Depth of pump in  
well. Ft. Bottom

Standing water-level  
(from surface)  
Ft. 88

Water-level when  
pumping Ft. 2 1/2 below

Water. End of test.  
Clear   
Cloudy \_\_\_\_\_  
Turbid \_\_\_\_\_

Was the well sterilized?  
Yes \_\_\_\_\_ No

To which laboratory was sample  
sent?  
\_\_\_\_\_

Date \_\_\_\_\_

Was the well sealed on comple-  
tion?  
Yes  No \_\_\_\_\_

How high did you leave the  
casing-pipe above grade?  
Level with  
cement.

Well was completed  
Date Dec 31 41

Well Constructor  
Joe Level  
Signature

Draw the diagram to show the  
right half only

618-2