

AUG 15 1976

State of Wisconsin
Department of Natural Resources
Box 450
Madison, Wisconsin 53701

NOTE:

White Copy - Division's Copy
Green Copy - Driller's Copy
Yellow Copy - Owner's Copy

WELL CONSTRUCTOR'S REPORT
Form 3300-15
Rev. 10-75

1. COUNTY Crawford CHECK (✓) ONE: Town Village City Eastman Name

2. LOCATION $\frac{1}{4}$ Section SW Section 36 Township 8N Range 7W 3. NAME OWNER AGENT AT TIME OF DRILLING CHECK (✓) ONE
 OR - Grid or Street No. Street Name 6 ADDRESS RFD

AND - If available subdivision name, lot & block No. POST OFFICE Grampa, WI 53826

4. Distance in feet from well to nearest: (Record answer in appropriate block) Building 40' Sanitary Bldg. Drain C.I. Other Sanitary Bldg. Sewer C.I. Other Floor Drain Connected To: C.I. Sewer Other Sewer Storm Bldg. Drain C.I. Other Storm Bldg. Sewer C.I. Other

Street Sewer San. Storm Other Sewers C.I. Other Foundation Drain Connected to: Sewage Sump C.I. Other Clearwater Sump Clearwater Dr. Clearwater Sump Clearwater Sump Holding Tank Sewage Absorption Unit 140' Seepage Pit Seepage Bed Seepage Trench

Privy Pet Waste Pit Pit: Nonconforming Existing Well Pump Tank Subsurface Pumproom Nonconforming Existing Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit

Temporary Manure Stack Watertight Liquid Manure Tank Solid Manure Storage Structure Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Other (Give Description)

5. Well is intended to supply water for: Country Home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
10	0 Surface	306	6	306	490

9. FORMATIONS

Kind	From (ft.)	To (ft.)
Clay	0 Surface	10
Limestone	10	240
Soft Sandstone	240	280
Hard Sandstone	280	450
Limestone	450	490

7. CASING, LINER, CURBING AND SCREEN
Material, Weight, Specification & Method of Assembly

Dia. (in.)	From (ft.)	To (ft.)
6	0 Surface	306

PE New Blacksteel 18.97
Valleysteel
Pitless Adaptor

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
Clay	0 Surface	8
Cement	8	306

10. TYPE OF DRILLING MACHINE USED

Cable Tool Rotary-hammer w/drilling mud & air Jetting with Air Water

Rotary-air w/drilling mud Rotary-hammer & air

Rotary-w/drilling mud Reverse Rotary

11. MISCELLANEOUS DATA

Yield Test: 3 Hrs. at 5 GPM

Depth from surface to normal water level 395 Ft.

Depth of water level when pumping 410 Ft. Stabilized Yes No

Well construction completed on Aug. 7 19 76

Well is terminated 10 inches above below final grade

Well disinfected upon completion Yes No

Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on Aug 11 19 76

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature 664
Kenneth Copien Registered Well Driller

Complete Mail Address
R3, Box 84 - Boscobel, WI 53805