

NOTE:

White Copy - Division's Copy  
 Green Copy - Driller's Copy  
 Yellow Copy - Owner's Copy

APR 13 1981

1. COUNTY Crawford CHECK (✓) ONE:  Town  Village  City Name Eastman

2. LOCATION NW 16 8N 5W 3. NAME  OWNER  AGENT AT TIME OF DRILLING CHECK (✓) ONE  
Mike Geisler  
 OR - Grid or Street No. Street Name ??? ADDRESS RR # 1  
 AND - If available subdivision name, lot & block No. POST OFFICE Eastman, WI

4. Distance in feet from well to nearest: (Record answer in appropriate block)

Building	Sanitary Bldg. Drain	Sanitary Bldg. Sewer	Floor Drain Connected To:	Storm Bldg. Drain	Storm Bldg. Sewer
<u>30'</u>	C.I. Other	C.I. Other	C.I. Sewer Other Sewer	C.I. Other	C.I. Other
		<u>60'</u>			

Street Sewer: San. Storm C.I. Other  
 Other Sewers: C.I. Other  
 Foundation Drain Connected to: Sewer Clearwater Dr. Sewage Sump Clearwater Sump  
 Sewage Sump: C.I. Other  
 Clearwater Sump  
 Septic Tank: 110'  
 Holding Tank  
 Sewage Absorption Unit: 130'  
 Seepage Pit  
 Seepage Bed  
 Seepage Trench

Privy: Pet Waste Pit Pit: Nonconforming Existing Well Pump Tank  
 Subsurface Pumproom: Nonconforming Existing  
 Barn Gutter  
 Animal Barn Pen  
 Animal Yard  
 Silo With Pit  
 Glass Lined Storage Facility  
 Silo w/o Pit  
 Earthen Silage Storage Trench Or Pit

Temporary Manure Stack: Watertight Liquid Manure Tank Solid Manure Storage Structure  
 Subsurface Gasoline or Oil Tank  
 Waste Pond or Land Disposal Unit (Specify Type)  
 Other (Give Description)

5. Well is intended to supply water for: Country Home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>183</u>	<u>6</u>	<u>183</u>	<u>300</u>	<u>clay</u>	<u>0</u>	<u>8</u>
						<u>limestone</u>	<u>8</u>	<u>235</u>
						<u>hard sandstone</u>	<u>235</u>	<u>300</u>

7. CASING, LINER, CURBING AND SCREEN  
 Material, Weight, Specification & Method of Assembly

Dia. (in.)	From (ft.)	To (ft.)
<u>6</u>	<u>Surface</u>	<u>183</u>

P.E. A-53 18.77/ft  
new black steel pitless adapter

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>clay</u>	<u>Surface</u>	<u>8</u>
<u>cement</u>	<u>8</u>	<u>183</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Rotary-hammer w/drilling mud & air  Jetting with  
 Rotary-air w/drilling mud  Rotary-hammer & air  Air  
 Rotary-w/drilling mud  Reverse Rotary  Water

Well construction completed on 10-3 1980

11. MISCELLANEOUS DATA

Yield Test: 3 Hrs. at 10 GPM Well is terminated 12 inches  above  below final grade

Depth from surface to normal water level 230 Ft. Well disinfected upon completion  Yes  No

Depth of water level when pumping 237 Ft. Stabilized  Yes  No Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on 4-6 1981

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature: Phil Coplain Registered Well Driller Complete Mail Address 308 E. Bluff  
Boscobel, WI 53805