

15132

WELL CONSTRUCTOR'S REPORT
FORM 3300-15

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
APR 2 1973
Box 430
Madison, Wisconsin 53701

NOTE

WHITE COPY - DIVISION'S COPY
GREEN COPY - DRILLER'S COPY
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE Town Village City NAME Seneca

2. LOCATION - 1/4 Section SE Section 27 Township 9N Range 5W

OR - Grid or street no. Street name

AND - If available subdivision name, lot & block no.

3. OWNER AT TIME OF DRILLING Mr. Tom Foley
ADDRESS R7D1
POST OFFICE Eastman, Wis., 54626

4. Distance in feet from well to nearest:

BUILDING C. I.	SANITARY SEWER TILE	FLOOR DRAIN C. I.	FOUNDATION DRAIN SEWER CONNECTED	FOUNDATION DRAIN INDEPENDENT	WASTE WATER DRAIN C. I.	WASTE WATER DRAIN TILE
	<u>12'</u>	<u>20'</u>				

(Record answer in appropriate block)

CLEAR WATER DRAIN C. I.	SEPTIC TANK TILE	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILLO	ABANDONED WELL	SINK HOLE
	<u>80'</u>		<u>95'</u>					

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Trailer home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>242</u>	<u>6</u>	<u>242</u>	<u>340</u>	<u>Clay</u>	<u>Surface</u>	<u>20</u>
						<u>soft sandstone</u>	<u>20</u>	<u>120</u>
						<u>broken limestone</u>	<u>120</u>	<u>230</u>
						<u>hard limestone</u>	<u>230</u>	<u>300</u>
						<u>sandstone</u>	<u>300</u>	<u>340</u>

7. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
<u>6</u>	<u>new black steel plain end 19.18</u>	<u>Surface</u>	<u>242</u>

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Clay</u>	<u>Surface</u>	<u>20</u>
<u>Cement</u>	<u>20</u>	<u>242</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool Direct Rotary Reverse Rotary
 Rotary - air w/drilling mud Rotary - hammer with drilling mud & air Jetting with Air Water

Well construction completed on 3-12- 19 73

11. MISCELLANEOUS DATA

Yield test: 3 Hrs. at 8 GPM

Well is terminated 10 inches above below final grade

Depth from surface to normal water level 280 ft. Well disinfected upon completion Yes No

Depth to water level when pumping 285 ft. Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on: 3-28- 19 73

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Beorneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS Boscobel, Wis., 53805
R3 Box 84

Please do not write in space below

COLIFORM TEST RESULT <u>789</u>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
------------------------------------	---------------	---------------	-----------	---------

REV. 3-71