

JUL 19 1976

NOTE:

White Copy - Division's Copy  
 Green Copy - Driller's Copy  
 Yellow Copy - Owner's Copy

1. COUNTY Crawford CHECK (✓) ONE:  Town  Village  City Name Clayton

2. LOCATION NE 34 10N 3W 3. NAME  OWNER  AGENT AT TIME OF DRILLING CHECK (✓) ONE  
 ADDRESS Ray Norton  
R7D2  
 POST OFFICE Gays Mills, Wis 54631

4. Distance in feet from well to nearest: (Record answer in appropriate block)

Building	Sanitary Bldg. Drain	Sanitary Bldg. Sewer	Floor Drain Connected To:	Storm Bldg. Drain	Storm Bldg. Sewer
<u>10'</u>	C.I. <u>20'</u> Other	C.I. Other	C.I. Sewer Other Sewer	C.I. Other	C.I. Other
Street Sewer	Other Sewers	Foundation Drain Connected to:	Sewage Sump	Clearwater Sump	Septic Tank
San. Storm	C.I. Other	Sewer Sewage Sump Clearwater Dr.	C.I. Other		Holding Tank
					Sewage Absorption Unit <u>65'</u>
					Seepage Pit
					Seepage Bed
					Seepage Trench

Privy  Pet Waste Pit  Pit: Nonconforming Existing  Well  Pump  Tank

Subsurface Pumphouse  Nonconforming Existing  Barn Gutter 100' Animal Barn Pen  Animal Yard  Silo With Pit  Glass Lined Storage Facility  Silo w/o Pit  Earthen Silage Storage Trench Or Pit

Temporary Manure Stack  Watertight Liquid Manure Tank  Solid Manure Storage Structure  Subsurface Gasoline or Oil Tank  Waste Pond or Land Disposal Unit (Specify Type)  Other (Give Description)

5. Well is intended to supply water for: Country home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
<u>10</u>	<u>0</u> Surface	<u>40</u>	<u>6</u>	<u>40</u>	<u>200</u>

9. FORMATIONS

Kind	From (ft.)	To (ft.)
<u>Clay</u>	<u>0</u> Surface	<u>30</u>
<u>limestone</u>	<u>30</u>	<u>80</u>
<u>hard shalestone</u>	<u>80</u>	<u>160</u>
<u>sandstone</u>	<u>60</u>	<u>200</u>

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification & Method of Assembly	From (ft.)	To (ft.)
<u>6</u>	<u>new black steel P.E 18.97 A-53</u>	<u>0</u> Surface	<u>40</u>
	<u>Valley Steel</u>		
	<u>Pitless adaptor</u>		

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Clay</u>	<u>0</u> Surface	<u>7</u>
<u>Cement</u>	<u>7</u>	<u>42</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Rotary-hammer w/drilling mud & air  Jetting with  Air  Water

Rotary-air w/drilling mud  Rotary-hammer & air

Rotary-w/drilling mud  Reverse Rotary

Well construction completed on 6-15- 19 76

11. MISCELLANEOUS DATA

Yield Test: 3 Hrs. at 5 GPM

Depth from surface to normal water level 150 Ft.

Depth of water level when pumping 158 Ft. Stabilized  Yes  No

Well is terminated 10 inches  above  below final grade

Well disinfected upon completion  Yes  No

Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on 7-13- 19 76

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Kenneth Coyman Registered Well Driller Complete Mail Address Boscobel R3 Box 84 Wi 53805