

JUL 1 - 1974

NOTE

WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY <i>Crawford</i>		CHECK ONE <input checked="" type="checkbox"/> Town <input type="checkbox"/> Village <input type="checkbox"/> City			NAME <i>Clayton</i>	
2. LOCATION - 1/4 Section <i>NE</i> Section <i>1</i> Township <i>10N</i> Range <i>4W</i>		3. OWNER AT TIME OF DRILLING <i>Jerry Brockway</i>				
OR - Grid or street no.		Street name		ADDRESS <i>R7D</i>		
AND - If available subdivision name, lot & block no.				POST OFFICE <i>Gays Mills, Wis., 54631</i>		
4. Distance in feet from well to nearest: (Record answer in appropriate block)		BUILDING C.I. <i>25'</i>	SANITARY SEWER C.I. <i>40'</i>	FLOOR DRAIN C.I.	FOUNDATION DRAIN SEWER CONNECTED	WASTE WATER DRAIN C.I.
CLEAR WATER DRAIN C.I.	SEPTIC TANK TILE	PRIVY	SEEPAGE PIT <i>70'</i>	ABSORPTION FIELD	BARN	SILLO
	<i>60'</i>				ABANDONED WELL	SINK HOLE

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: *Country home*

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<i>6</i>	<i>Surface</i>	<i>100</i>				<i>loose sand</i>	<i>Surface</i>	<i>50</i>
						<i>sandstone</i>	<i>50</i>	<i>100</i>
7. CASING, LINER, CURBING, AND SCREEN								
Dia. (in.)	Kind and Weight		From (ft.)	To (ft.)				
<i>6</i>	<i>new black steel plain end 18.97</i>		<i>Surface</i>	<i>62</i>				

8. GROUT OR OTHER SEALING MATERIAL			10. TYPE OF DRILLING MACHINE USED		
Kind	From (ft.)	To (ft.)	<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary
<i>loose sand</i>	<i>Surface</i>	<i>50</i>	<input type="checkbox"/> Rotary - air w/drilling mud	<input checked="" type="checkbox"/> Rotary - hammer with drilling mud & air	<input type="checkbox"/> Jetting with <input type="checkbox"/> Air <input type="checkbox"/> Water
			Well construction completed on <i>6-12-1974</i>		

11. MISCELLANEOUS DATA		Well is terminated <i>16</i> inches <input checked="" type="checkbox"/> above <input type="checkbox"/> below final grade
Yield test: <i>3</i> Hrs. at <i>8</i> GPM	Well disinfected upon completion <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Well sealed watertight upon completion <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Depth from surface to normal water level <i>70</i> ft.		
Depth to water level when pumping <i>70</i> ft.		

Water sample sent to *Madison* laboratory on: *6-26-1974*

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE <i>Kenneth Coyran</i> Registered Well Driller	COMPLETE MAIL ADDRESS <i>Boysenel R3 Box 84 Wis., 53805</i>
---	--

Please do not write in space below

COLIFORM TEST RESULT <i>888</i>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
------------------------------------	---------------	---------------	-----------	---------