

NOTE:

White Copy - Division's Copy  
 Green Copy - Driller's Copy  
 Yellow Copy - Owner's Copy

MAY 29 1979

1. COUNTY Crawford CHECK (✓) ONE:  Town  Village  City Name Freeman

2. LOCATION SW Section 7 Township 10N Range 6W 3. NAME  OWNER  AGENT AT TIME OF DRILLING CHECK (✓) ONE Sylvester Zobeck  
 OR - Grid or Street No. Street Name ADDRESS R1

AND - If available subdivision name, lot & block No. POST OFFICE Ferrisville, Wisc. 54628

4. Distance in feet from well to nearest: (Record answer in appropriate block) 10'  
 Building Sanitary Bldg. Drain Sanitary Bldg. Sewer Floor Drain Connected To: Storm Bldg. Drain Storm Bldg. Sewer  
 C.I. Other C.I. Other C.I. Sewer Other Sewer C.I. Other C.I. Other

Street Sewer Other Sewers Foundation Drain Connected to: Sewage Sump Clearwater Sump Septic Holding Sewage Absorption Unit 80'  
 San. Storm C.I. Other Sewer Sewage Sump C.I. Other Clearwater Sump Septic Tank Holding Tank Seepage Pit Seepage Bed Seepage Trench

Privy Pet Waste Pit Pit: Nonconforming Existing Subsurface Pumproom Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit  
225' 270'

Temporary Manure Stack Watertight Liquid Manure Tank Solid Manure Storage Structure Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Other (Give Description)

5. Well is intended to supply water for: Farm home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
10	Surface	252	6	252	520

9. FORMATIONS

Kind	From (ft.)	To (ft.)
Clay	Surface	8
limestone	8	160
soft sandstone	160	230
hard shalestone	230	460
hard sandstone	460	520

7. CASING, LINER, CURBING AND SCREEN  
 Material, Weight, Specification & Method of Assembly From (ft.) To (ft.)  
6 new black steel 0 252  
Valley Steel Surface  
P.E. 18.97  
A-53  
Morrison head

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
Clay	Surface	7
Cement	7	252

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Rotary-hammer w/drilling mud & air  Jetting with  Air  Water

Rotary-air w/drilling mud  Rotary-hammer & air

Rotary-w/drilling mud  Reverse Rotary

11. MISCELLANEOUS DATA  
 Yield Test: 3 Hrs. at 5 GPM  
 Depth from surface to normal water level 400 Ft.  
 Depth of water level when pumping 4.15 Ft. Stabilized  Yes  No

Well construction completed on 4-30- 19 79  
 Well is terminated 12 inches  above final grade  below  
 Well disinfected upon completion  Yes  No  
 Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on 5-21- 19 79

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Kenneth Coplan Registered Well Driller Complete Mail Address R3 Box 84 Boscobel, Wisc. 53805